



FINISHED OPENING SIZE: (W) (H)

Insulated Foam Panel Thickness
40mm 60mm 80mm

Vision Window Height
(standard no window)
220mm 440mm 660mm

UL LISTED OPERATOR INPUT POWER
220V-240V SINGLE PHASE

CONTROLS:

STEP CONTROL (PULL TO OPEN, PULL TO CLOSE)
TIMER TO CLOSE (PULL TO OPEN, TIME DELAY TO COLSE)
3-BUTTON CONTROL (OPEN, COLSE, STOP)
RADOR OPEN AND TIMER CLOSE
FLOOR LOOP OPEN AND TIMER CLOSE
REMOTE CONTROL

SAFETY DEVICES:

BOTTOM SAFETY EDGE AND
SAFETY BEAM ARE STANDARD
LIGHT CURTAIN
EXTRA SAETY BEAM

MOUNTING FASTENERS:

CONCRETE ANCHOR
METAL JAMBS

OPTIONS:

HEADER HOOD
STAINLESS STEEL TRACK
COVER AND HEADER HOOD

OTHER REQUIRED OPTIONS:

QUANTITY:

M/F:

CUSTOMER:

JOB:

DATE:

SIGNATURE:

QUOTE: ORDER: #:

TDK HSR High Speed Spiral
Roll Up Door Shop Drawing